

UNIDRAIN TENDER DESCRIPTION | CORNER FLOOR DRAIN

Unidrain ClassicLine

Corner floor drain with wall flange and frame and grating in stainless steel.

The drain's upper edge is fitted level with the upper edge of the floor surface.

Dimensions at floor surface: triangular, with side lengths 193 x 193 x 270 mm

Material: All visible parts in stainless steel (AISI 304).

Grating: hole patterns with <circular/columns with vertical> holes.

Outlet unit: Polypropylene Ø <32,50,75> with <horizontal/vertical> outlet, <with/without> water trap and <with/without> side inlet.

The drain must be approved according to European Standard EN 1253.

Unidrain HighLine

Corner floor drain with wall flange <with/without> frame and panel in steel.

The drain's upper edge is fitted level with the upper edge of the floor surface.

Dimensions at floor surface (with frame): triangular, with side lengths 193 x 193 x 270 mm

Dimensions at floor surface (without frame): triangular, with side lengths 193 x 193 x 270 mm

Material: panel in stainless steel (AISI 304)

Panel: Solid panel triangle installed with a uniform 6 mm offset from the frame/tiles.

Outlet unit: Polypropylene Ø <32,50,75> with <horizontal/vertical> outlet, <with/without> water trap and <with/without> side inlet.

The drain must be approved according to European Standard EN 1253.