

# UNIDRAIN TENDER DESCRIPTION | LINEAR FLOOR DRAIN

## Unidrain ClassicLine

Linear floor drain with wall flange and frame and grating in stainless steel.

The drain's upper edge is fitted level with the upper edge of the floor surface.

**Dimensions at floor surface:** Length: <315;695;795;895;995;1195> mm, Width: 80 mm

**Material:** All visible parts in stainless steel (AISI 304).

**Grating:** hole patterns with <circular; rectangular; columns with vertical; columns with horizontal> holes.

**Outlet unit:** Polypropylene Ø <32;50;75> with <horizontal; vertical> outlet, <with; without> water trap and <with; without> side inlet Ø40 mm.

The drain must be approved according to European Standard EN 1253.

## Unidrain Highline

Linear floor drain with wall flange <with; without> frame and <brushed steel panel; polished steel panel; steel panel in copper PVD; steel panel in brass PVD; steel panel in black PVD; panel for tile; cassette panel>

The drain's upper edge is fitted level with the upper edge of the floor surface. Must be installed directly against the back wall.

**Dimensions at floor surface (with frame):**

Length: <315;695;795;895;995;1195> mm, Width: 74 mm

**Dimensions at floor surface (without frame):**

Length without frame: <253; 633; 733; 833; 933; 1133> Width: 37 mm

**Material:** panel in <stainless steel (AISI 304); tile as floor surface; cassette> and <with; without> frame.

**Outlet unit:** Polypropylene Ø <32; 50; 75> mm with <horizontal; vertical> outlet, <with; without> water trap and <with; without> side inlet Ø40.

The drain must be approved according to European Standard EN 1253.