

UNIDRAIN TENDER DESCRIPTION | LINEAR FLOOR DRAIN

Unidrain ClassicLine

Linear floor drain with wall flange and frame and grating in stainless steel.

The drain's upper edge is fitted level with the upper edge of the floor surface.

Dimensions at floor surface: Length: <315;596;695;795;895;995;1195> mm, Width: 80 mm

Material: All visible parts in stainless steel (AISI 304).

Grating: hole patterns with <circular; rectangular; columns with vertical; columns with horizontal> holes.

Outlet unit: Polypropylene Ø <32;50;75> with <horizontal; vertical> outlet, <with; without> water trap and <with; without> side inlet Ø40 mm.

The drain must be approved according to European Standard EN 1253.

Unidrain Highline

Linear floor drain with wall flange <with; without> frame and <brushed steel panel; polished steel panel; steel panel in copper PVD; steel panel in brass PVD; steel panel in black PVD; panel for tile; cassette panel>

The drain's upper edge is fitted level with the upper edge of the floor surface. Must be installed directly against the back wall.

Dimensions at floor surface (with frame):

Length: <315;695;795;895;995;1195> mm, Width: 74 mm

Dimensions at floor surface (without frame):

Length without frame: <253; 633; 733; 833; 933; 1133> Width: 37 mm

Material: panel in <stainless steel (AISI 304); tile as floor surface; cassette> and <with; without> frame.

Outlet unit: Polypropylene Ø <32; 50; 75> mm with <horizontal; vertical> outlet, <with; without> water trap and <with; without> side inlet Ø40.

The drain must be approved according to European Standard EN 1253.